

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



PCT

(43) International Publication Date
5 January 2006 (05.01.2006)

(10) International Publication Number
WO 2006/001610 A1

(51) International Patent Classification⁷:

A47L 15/42

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/KR2005/001690

(22) International Filing Date:

7 June 2005 (07.06.2005)

(25) Filing Language:

Korean

(26) Publication Language:

English

(30) Priority Data:

10-2004-0047447 24 June 2004 (24.06.2004) KR
10-2004-0047446 24 June 2004 (24.06.2004) KR

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant (for all designated States except US): LG ELECTRONICS, INC. [KR/KR]; 20 Yoido-dong, Youngdungpo-gu, Seoul 150-875 (KR).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LEAKAGE PREVENTING STRUCTURE OF DISH WASHER



(57) Abstract: A leakage preventing structure of a dishwasher is provided. The structure includes a wash motor with a motor shaft disposed at its center, a sump housing that the motor shaft passes through, and a sealing portion that seals the space between the wash motor and the sump housing. The sealing portion is an aircap that controls the water level of washing water introduced into the aircap by means of air pressure of air inside the aircap, or a sealing member coupled to the motor shaft of the wash motor.

WO 2006/001610 A1